

# Bush Hog® TOUGH

## 4045 Quick Attach Mid-Mount Loaders

### Skid Steer Quick Attach System

#### BUSH HOG® TOUGH FEATURES

**TOUGH** Boxed Boom Design

**TOUGH** Large Diameter Cross Tubes

**TOUGH** Robotic Welds

**TOUGH** High Strength Chrome Plated  
Cylinder Rods

**TOUGH** Steel Tube Hydraulic Lines

**TOUGH** Pivot Pins With Recessed Grease Zerk

**TOUGH** Bush Hog Made Bucket

**TOUGH** Powder Coat Paint



MODEL	Specifications Based on 1997 ASAE STANDARDS	4045
Tractor PTO HP Range		40 - 70
2WD/FWA		2WD/FWA
Maximum Lift Height - Measured at Pivot Pin		126 inches
Maximum Lift Height - Under Level Bucket		116 inches
Maximum Dump Angle		45°
Digging Depth		3.5 inches
Lift Capacity to Maximum Height - At Pivot Pin		3500 lbs
Lift Capacity to Maximum Height - 31.5 inches Forward of Pivot Pin		2200 lbs
Lift Capacity to 59 inch Height - At Pivot Pin		4100 lbs
Lift Capacity to 59 inch Height - 31.5 inches Forward of Pivot Pin		2950 lbs
Breakout Force - At Pivot Pin		5000 lbs
Breakout Force - 31.5 inches - Forward of Pivot Pin		3500 lbs
Rollback Force at Maximum Height - 31.5 inches Forward of Pivot Pin		5100 lbs
Rollback Force at 59 inch Height - 31.5 inches Forward of Pivot Pin		5300 lbs
Rollback Force at Ground Level - 31.5 inches Forward of Pivot Pin		3600 lbs
Raising Time (Ground Level to Full Height)		5 seconds
Lowering Time (Full Height to Ground Level)		3 seconds
Bucket Dumping Time (Full Rollback to Full Dump)		5 seconds
Bucket Rollback Time (Full Dump to Full Rollback)		3 seconds
Hydraulics	Two 2.5 inch Bore, 23.38 inch Stroke Double Acting Bucket Cylinders and Two 2.75 inch Bore, 18.25 inch Stroke Double Acting Lift Cylinders	
Specifications Based on Tractor System of	2850 PSI hyd. pressure & 11 GPM pump capacity	
Regular Duty Skid Steer Buckets	Available in 72, 80 and 84 inch widths	
Commercial Grade Skid Steer Buckets	Available in 60, 72 and 84 inch widths	
Options	Forklift Attachment (48 inch tines), Round Bale Spear, Dual-Probe Bale Spear, Grapple Fork, Bucket Tine Teeth, Bolt-On Digging Teeth, Side Cutting Edges, Spill Guard Attachment, Hydraulic Self-Leveling, and Grill Guards	
Warranty	1 year limited warranty	

#### FEATURES

“Universal” skid steer quick attach system compatible with skid steer syle attachments,  
Available in major tractor colors

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE